



GREEN Series HMI

GL043/GL043E

Product Features:

- Industrial grade CPU, 800MHz, 128M DDR3;
- 4.3", high-definition display, 16.77 million true colors;
- Ultra-thin body design for only 33mm, perfect chose for small-sized installation space demand;
- Sealing design of buckle for waterproof and oil resistance.



The GREEN series cooperates with new generation free configuration software: **Kinco DTools**.

It supports four languages versions of Chinese, English, Korean and Russian.

The configuration design content supports all fonts installed in computer system.

It supports cloud monitoring. VNC achieves interoperation between HMI and HMI, HMI and PC, mobile phones(or other terminals), supports convenient components such as installment, PDF browsing and operating log records for designing guiding interface.

It is the humanized design and easy to use.

GREEN Series HMI

GL043/GL043E



Model	GL043	GL043E	Mechanical Dimensions (Unit : mm)
Performance specification			
Display size	4.3" TFT		
Display area	95.04mm(W)x53.86mm(H)		
Resolution	480*272 pixels		
Display color	16.7M color		
Display angle of view	70/70/50/70(left/right/up/down)		
Contrast ratio	500:1		
Backlight	LED		
Brightness	450cd/m ²		
Backlight life	More than 30000 hours		
Touch panel	4 line precision resistance network (surface hardness 4H)		
CPU	ARM RISC 32Bit 800MHz		
Storage	128MB NAND Flash Memory+128MB DDR3 Memory		
RTC	Built-in		
Extensible memory	None		
Print port	Serial port		
Ethernet	None	10/100M self-adaption	
Program download	USB Slave(Micro USB) / Serial port	USB Slave(Micro USB) /Serial port/Ethernet	
Communication port	COM0:RS232/RS485/RS422; COM2:RS232		
Electrical specifications			
Input power supply	DC10V ~ DC28V		
Rated power	2W @24V DC		
Allowable loss of power	<3ms		
Insulation resistance	Over 50MΩ@500V DC		
Hi-pot test	500 VAC 1 minute		
Structure specifications			
Shell material	Engineering plastic		
Shape size	132mm*102mm*33mm		
Cutout size	119mm*93mm		
Weight	0.21Kg		
Environmental specifications			
Temperature of working environment	0 ~ 50 °C		
Humidity of working environment	10 ~ 90 % RH (non-condensing)		
Storage environment temperature	-20 ~ 60°C		
Storage environment humidity	10 ~ 90 % RH (non-condensing)		
Sine vibration test	10 ~ 500Hz, 30m/s ² , X, Y, Z direction/hour		
Cooling mode	Natural air cooling		
Product certification			
Panel protection grade	Conforming to IP65 certification(4208—93)		
CE authentication	EN61000-6-4:2007+A1:2011, EN61000-6-2:2005		
Software			
Configuration software	Kinco DTools V3.3 and above		

Kinco® Automation

www.en.kinco.cn Email:sales@kinco.cn

(All trademarks and logos are property of and registered by their respective owners.)